

Claims

What is claimed is:

5
10
15
20
25
30

1. A composite blade, in which there is an essentially plate-like blade component with a composite-construction and retention members arranged in its rear part, and which blade is intended to be installed in a special blade holder with the said retention members remaining in the throat of the blade holder, characterized in that the retention members are formed of profiling arranged as a lateral extension of the blade component, which profiling extends essentially over the entire length of the blade and which is of the same piece as the blade component.

2. A blade according to claim 1, characterized in that the profiling is essentially uniform in cross-section and extends on both sides of the blade component over the thickness of the blade component.

3. A blade according to claim 1, characterized in that the profiling has a non-uniform cross-section and the protruding parts of the profiling are formed to be flexible.

4. A blade according to claim 1, characterized in that the profiling has a hollow cross-section, in which case a medium connection is arranged to the upper and/or lower side of the blade component from the interior space of the profiling thus formed.

5. A blade according to claim 1, characterized in that the composite material contains reinforcing fibers, arranged essentially in the lateral direction of the blade.

0970120460

Sub
A17

7. A method for manufacturing a composite blade, in which method an essentially plate-like blade component is formed from composite material, and retention members are arranged in the rear part of the blade component to retain the blade in the throat of a special blade holder, characterized in that a unified blank is formed from composite material, to that both the blade component and the profiling forming the retention members are manufactured simultaneously, and from which blank the blade with its retention members is detached.

9. A method according to claim 7, characterized in that two or more blades and their corresponding profiling are formed in the blank.

10. A method according to claims 7, characterized in that holes or similar, arranged according to the blade-moving devices to be used, are machined in the upper and/or lower surface of the profiling.